

## Product Description

<b>Product Name:</b>	Corrugated Switchboard Mat
<b>Description:</b>	ASTM D-178 - Type II, Class 2
<b>Surface Configuration:</b>	Top - Corrugated Bottom - Knurled W/ certification engraved
<b>Thickness:</b>	¼" Minimum
<b>Chemical Resistance:</b>	Excellent chemical resistance to many commercial and Industrial chemicals. Please call for specific recommendations.

## Physical Properties

<u>Characteristics</u>	<u>Performance</u>	<u>Test Method</u>
Tensile Strength	700 psi	ASTM-D-412
Elongation	250%	ASTM-D-412
Moisture Absorption	.08%	ASTM-D-570
Flammability	Pass	ASTM-D-1692
Ozone Resistance	Pass	ASTM-D-1149, Method A
Accelerated Aging	90% of Original	ASTM-D-573
Oil Resistance	.5% Volume Increase	ASTM-D-471

## Electrical Properties

Dielectric Test Voltage	30,000 VAC	ASTM-D-178
Proof Test Over Entire Surface at	20,000 VAC	ASTM-D-178
Recommended Max Use Voltage	17,000 VAC	ASTM-D-178

**A**  
**CFW Flooring, Inc.**  
**Company**

**CFW Flooring, Inc. 38325 6th St. East, Palmdale, CA 93550**  
**Tel. 1-661-273-8700, 1-661-273-8701 Fax: 1-661-885-8300**